Found County Monument N89° 05' 04" E 5257.00 € E 1/4 Cor. Found original marked stone at W/4 Cor. Set County Monument C'/4 Cor. Found 5/8" rebar Not set set by previous survey NE Cor. SE/4 of SW/4 Point of Beginning Set 5/8" x 24" rebar w/ Plastic cap st at 51/16 Cor. 589°27'21W 2623.65 450.00' 16 Cor Not Set B 6.23 ACS. Sec 34 Sec 35 Sec 2 N89°49'46"E 2615.70 5 1/4 Cor Found B.L.M. Found monument aluminum monument spike set from B.L.M. references North 1"=200

- 1 1 1

PROPERTY SURVEY FOR

NORMAN JENKINS

SECTION 35, TOWNSHIP 3 SOUTH, RANGE 5 WEST

UINTAH SPECIAL BASE AND MERIDIAN

DESCRIPTION OF PARCEL A


Beginning at the Northeast Corner of the Southeast Quarter of the Southwest Quarter of Section 35, Township 3 South, Range 5 West of the Uintah Special Base and Meridian; Thence South 30° 33' 22" West 823.25 feet; Thence South 58° 50' 19" East 203.50 feet; Thence South 29° 04' 03" West 160.20 feet, more or less to a point on the North right-of-way line of the County Road and the centerline of an existing driveway; Thence Southeasterly 446.73 feet, more or less along said right-of-way to the East line of said Southeast Quarter; Thence North 0° 25' 06" West (North, by record) 1252.43 feet along said East line to the POINT OF BEGINNING; said described tract containing 6.23 acres, more or less; with a bearing of North 0° 25' 06" West from the South Quarter Corner to the North Quarter Corner of said Section being used as the basis of bearings.

DESCRIPTION OF PARCEL B

Beginning at the Northeast Corner of the Southeast Quarter of the Southwest Quarter of Section 35, Township 3 South, Range 5 West of the Uintah Special Base and Meridian; Thence South 89° 27' 21" West (West, by record) 450.00 feet along the North line of said Southeast Quarter; Thence South 0° 25' 06" East, parallel with the East line of said Southeast Quarter, (South, by record) 400.00 feet; Thence South 89° 27' 21" West, parallel with said North line, (West, by record) 150.00 feet; Thence South 0° 25' 06" East (South, by record) 386.96 feet, more or less to the North right-of-way line of the County Road; Thence Southeasterly 316.75 feet along said right-of-way line to the centerline of an existing driveway; Thence North 29° 04' 03" East 160.20 feet to a rebar; Thence North 58° 50' 19" West 203.50 feet to a rebar;
Thence North 30° 33' 22" East 823.25 feet to the POINT OF BEGINNING; said described tract containing 6.00 acres, more or less; with a bearing of North 0° 25' 06" West from the South Quarter Corner to the North Quarter Corner being used as the basis of bearings.

SURVEYOR'S CERTIFICATE

This is to certify that I have surveyed the parcels of land shown on this plat, and that the monuments indicated were found or set during said survey, and that this plat accurately represents said survey to the best of my knowledge.



Jerry D. Allred, Registered Land Surveyor, Cert. No. 148951 (Utah)

Duchesne Co. Surveyors File # 390

JERRY D. ALLRED & ASSOCIATES
Surveying & Engineering Consultants

121 North Center Street P.O. Box 975 DUCHESNE, UTAH 84021 (801) 738-5352

11 June 194 94-100-032